

Eco Types: DILM15, DILM38, DILM72, DILM170

				DILM15	DILM17		DILM38	DILM40		DILM72	DILM80		DILM170	DILM185
AC-3	Motor rating	P	kW	7.5	7.5		18.5	18.5		37	37		90	90
	Rated current 400 V	I_e	A	15.5	18		38	40		72	80		170	185
	Electrical life span at I_e		10^6 Sch	0.75	1.3		0.5	1.3		0,75	1,3		0,75	1,3
AC-4	Motor rating	P	kW	3	4.5		7	9		12	20		33	75
	Rated current 400 V	I_e	A	7	10		15	18		25	40		65	136
	Electrical life span at I_e		10^6 Sch	0.2	0.2		0.2	0.2		0,2	0,2		0.2	0,04
AC-1	Conv. therm.current at 40°C	I_{th}	A	22	40		45	60		98	110		225	337
	Conv. therm.current at 60°C	I_{th}	A	20	35		40	50		80	90		185	275
Dimensions														
	Width		mm	45	45		45	55		55	90		90	140
	High		mm	68	85		85	115		115	170		170	180
	Depth		mm	75	98		98	132		132	160		160	208
Integrated Auxiliary contact				1 NO or 1 NC	1 NO or 1 NC		1 NO or 1 NC	–		–	–		–	2 NO and 2 NC
Overload relay for direct mounting				ZB12-16	ZB32-16		ZB32-38	ZB65-40		ZB65-75	ZB150-100		ZB150-175	Z5-160/FF250 Z5-220/FF250