

Frame sizes Types to IEC60947	<b>IZM X16</b> 630 A, 800 A, 1000 A, 1250 A, 1600 A	<b>IZM 20</b> 800 A, 1000 A, 1250 A, 1600 A, 2000 A	<b>IZM 32</b> 800 A, 1000 A, 1250 A, 1600 A, 2000 A, 2500 A, 3200 A	<b>IZM 40</b> 4000 A	<b>IZM 63</b> 4000 A, 5000 A, 6300 A
<b>Maximum switching capacity at:</b> $U_e$ 415V/690V: $I_{cu}$ (kA) $I_{cs}$ (kA) $I_{cw}$ (kA)	65/42 50/42 42/42	65/65 65/65 65/65	100/100 100/85 85/85	100/100 100/100 100/85	100/100 100/100 100/100
<b>Dimensions</b>					
Fixed type					
Width 3-pole (mm)	210	318	410	640	887
Width 4-pole (mm)	280	413	537	830	1120
Height (mm)	335	426			
Depth (mm)	182	372			
Drawer unit					
Width 3-pole (mm)	255	336	432	675	909
Width 4-pole (mm)	322	432	559	870	1036
Height (mm)	360	525			
Depth (mm)	272	475			
<b>Section width for xEnergy (up to 4000 A) and MODAN (up to 6300 A) switchboards</b>					
Fixed type					
Width 3-pole (mm)	400	600	600	1000	1200
Width 4-pole (mm)	600	800	800	1000	1400
Drawer unit					
Width 3-pole (mm)	400	600	600	1000	1200
Width 4-pole (mm)	600	800	800	1000	1400